

# AGGLOTECH

The finest AGGLOTECH surfaces can be kept at their beautiful best if you protect them with FILA. Specially developed products, that **don't change the materials' appearance because they don't create a surface film**, and maintain all the stone's original beauty.

*Choosing AGGLOTECH means using a reconstituted stone made by means of an exclusive process, which skilfully blends natural ingredients – marble chips, Portland cement and water. Its capability for creating customised materials, uniform colour and high production capacity make AGGLOTECH an ideal partner for major construction projects.*



## WASHING AFTER LAYING

**FILA CLEANER** (coverage: 50 m<sup>2</sup>; dilution 1:20)

After laying is complete, the floor must be washed thoroughly to remove all laying residues, such as grout, adhesive, etc... For this purpose Fila recommends **FILA CLEANER** neutral detergent diluted 1:20. Avoid using acids. Even if diluted, acids tend to corrode the surface.



## NATURAL FINISH STAIN PROTECTION

**FILAMP90 ECO PLUS** (water-based, coverage: 10-20 m<sup>2</sup>; undiluted) o **FILAMP90** (solvent-based, coverage: 10-20 m<sup>2</sup>; undiluted).

Spread a coat of **FILAMP90 ECO PLUS** over a clean and dry floor and apply a second coat 4 hours after the first. The surface can be walked on after 8/12 hours. If using **FILAMP90**, the surface must be completely dry.

Apply the second coat 24 hours after the first.



## FINISHING

**FILAMATT**, **FILASATIN**, **FILALONGLIFE** (coverage: 30 m<sup>2</sup>; undiluted)

Choose the finishing wax depending on the degree of gloss required:

Use **FILAMATT** for a natural/matt effect finish, **FILASATIN** for a satiny look, or **FILALONGLIFE** for a gloss effect. Apply one or two coats (depending on absorption) of the chosen wax with a rag or waxing fleece. Leave to dry for about one hour.

When using **FILASATIN**, we recommend polishing, if a higher level of gloss is desired.



## MAINTENANCE

**FILA CLEANER** (coverage: 1500 m<sup>2</sup>; dilution 1:200)

For everyday cleaning, dilute **FILA CLEANER** 1:200 in water. Highly diluted does not require rinsing. Increase the quantity of product in the solution up to 1:30 - 1:50 for a deeper clean or in case of stubborn dirt.

To renew shine wipe from time to time with a solution of finishing wax.



## EXTRAORDINARY MAINTENANCE

**FILAPS87** (coverage: 20 m<sup>2</sup>; dilution 1:5)

Remove the worn protective layer and dirt using **FILAPS87**. When the floor is clean and dry, reapply two coats of the finishing wax.

Remove any stains using **FILASR95** or **FILANO SPOT** stain removers. Treatment does not protect the material from acid attack.



**Fila Industria Chimica Spa**  
Via Garibaldi 58 - 35018 San Martino di Lupari (PD)  
Tel. +39 049.9467300 Fax +39 049.9460753  
info@filsolutions.com - [filsolutions.com](http://filsolutions.com)



**Agglotech Spa**  
Via Monte Santa Viola 16, I-37142 Verona  
tel +39 045 551777 fax +39 045 8801123  
info@agglotech.com - [www.agglotech.com](http://www.agglotech.com)



Green Care is Fila's major project for the protection of the environment: a multiplicity of eco-friendly actions the company implements at all levels, from production to solutions, and from the use to the disposal of products.